


Chapter 1 Introduction



*Computer Networking:
A Top Down Approach ,
4th edition.*
Jim Kurose, Keith Ross
Addison-Wesley, July
2007.

A note on the use of these ppt slides:

We're making these slides freely available to all (faculty, students, readers). They're in PowerPoint form so you can add, modify, and delete slides (including this one) and slide content to suit your needs. They obviously represent a *lot* of work on our part. In return for use, we only ask the following:

- If you use these slides (e.g., in a class) in substantially unaltered form, that you mention their source (after all, we'd like people to use our book!)
- If you post any slides in substantially unaltered form on a www site, that you note that they are adapted from (or perhaps identical to) our slides, and note our copyright of this material.

Thanks and enjoy! JFK/KWR

All material copyright 1996-2007
J.F Kurose and K.W. Ross, All Rights Reserved

Introduction 1-1

Chapter 1: Introduction

Our goal:

- get "feel" and terminology
- more depth, detail *later* in course
- approach:
 - ❖ use Internet as example

Overview:

- what's the Internet?
- what's a protocol?
- network edge; hosts, access net, physical media
- network core: packet/circuit switching, Internet structure
- performance: loss, delay, throughput
- protocol layers, service models

Introduction 1-2

Chapter 1: roadmap

1.1 What is the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core


- circuit switching, packet switching, network structure

1.4 Delay, loss and throughput in packet-switched networks

1.5 Protocol layers, service models

Introduction 1-3

What's the Internet: "nuts and bolts" view



Introduction 1-4


"Cool" internet appliances



IP picture frame
<http://www.ceiva.com/>



Web-enabled toaster +
weather forecaster




World's smallest web server
<http://www-ccs.cs.umass.edu/~shri/iPic.html>



Internet phones


What's the Internet: "nuts and bolts" view

- *protocols* control sending, receiving of msgs
 - ❖ e.g., TCP, IP, HTTP, Skype, Ethernet
- **Internet: "network of networks"**
 - ❖ loosely hierarchical
 - ❖ public Internet versus private intranet
- Internet standards
 - ❖ RFC: Request for comments
 - ❖ IETF: Internet Engineering Task Force



What's the Internet: a service view

- **communication infrastructure** enables distributed applications:
 - ❖ Web, VoIP, email, games, e-commerce, file sharing
- **communication services provided to apps:**
 - ❖ reliable data delivery from source to destination
 - ❖ "best effort" (unreliable) data delivery



What's a protocol?

human protocols:

- "what's the time?"
- "I have a question"
- introductions

... specific msgs sent
... specific actions taken when msgs received, or other events


network protocols:

- machines rather than humans
- all communication activity in Internet governed by protocols

protocols define format, order of msgs sent and received among network entities, and actions taken on msg transmission, receipt

What's a protocol?

a human protocol and a computer network protocol:



Q: Other human protocols?

Chapter 1: roadmap

1.1 What is the Internet?

1.2 Network edge

- end systems, access networks, links

1.3 Network core


- circuit switching, packet switching, network structure

1.4 Delay, loss and throughput in packet-switched networks

1.5 Protocol layers, service models

A closer look at network structure:

- network edge: applications and hosts
- access networks, physical media: wired, wireless communication links
- network core:
 - ❖ interconnected routers
 - ❖ network of networks



The network edge:

□ end systems (hosts):


- ❖ run application programs
- ❖ e.g. Web, email
- ❖ at "edge of network"

□ client/server model

- ❖ client host requests, receives service from always-on server
- ❖ e.g. Web browser/server; email client/server

□ peer-peer model:

- ❖ minimal (or no) use of dedicated servers
- ❖ e.g. Skype, BitTorrent



Network edge: reliable data transfer service

Goal: data transfer

between end systems

- ❑ **handshaking:** setup (prepare for) data transfer ahead of time
 - ❖ Hello, hello back human protocol
 - ❖ **set up "state"** in two communicating hosts
- ❑ TCP - Transmission Control Protocol
 - ❖ Internet's reliable data transfer service

TCP service [RFC 793]

- ❑ **reliable, in-order** byte-stream data transfer
 - ❖ loss: acknowledgements and retransmissions
- ❑ **flow control:**
 - ❖ sender won't overwhelm receiver
- ❑ **congestion control:**
 - ❖ senders "slow down sending rate" when network congested

Introduction 1-13

Network edge: best effort (unreliable) data transfer service

Goal: data transfer

between end systems

- ❖ same as before!
- ❑ **UDP** - User Datagram Protocol [RFC 768]:
 - ❖ connectionless
 - ❖ unreliable data transfer
 - ❖ no flow control
 - ❖ no congestion control

App's using TCP:

- ❑ HTTP (Web), FTP (file transfer), Telnet (remote login), SMTP (email)

App's using UDP:

- ❑ streaming media, teleconferencing, DNS, Internet telephony

Introduction 1-14


Access networks and physical media

Q: How to connect end systems to edge router?

- ❑ residential access nets
- ❑ institutional access networks (school, company)
- ❑ mobile access networks

Keep in mind:

- ❑ bandwidth (bits per second) of access network?
- ❑ shared or dedicated?




Introduction 1-15

Residential access: point to point access

❑ **Dialup via modem**

- ❖ up to 56Kbps direct access to router (often less)
- ❖ Can't surf and phone at same time: can't be "always on"



❑ **DSL: digital subscriber line**


- ❖ deployment: telephone company (typically)
- ❖ up to 1 Mbps upstream (today typically < 256 kbps)
- ❖ up to 8 Mbps downstream (today typically < 1 Mbps)
- ❖ dedicated physical line to telephone central office

Introduction 1-16


Residential access: cable modems

- **HFC: hybrid fiber coax**
 - ❖ asymmetric: up to 30Mbps downstream, 2 Mbps upstream
- **network** of cable and fiber attaches homes to ISP router
 - ❖ homes share access to router
- **deployment:** available via cable TV companies


Residential access: cable modems




Cable Network Architecture: Overview



Cable Network Architecture: Overview




Cable Network Architecture: Overview



Introduction 1-21


Cable Network Architecture: Overview



Introduction 1-22

Company access: local area networks


- ❑ company/univ **local area network** (LAN) connects end system to edge router
- ❑ **Ethernet:**
 - ❖ 10 Mbs, 100Mbps, 1Gbps, 10Gbps Ethernet
 - ❖ modern configuration: end systems connect into *Ethernet switch*
- ❑ LANs: chapter 5



Introduction 1-23

Wireless access networks

- ❑ shared *wireless access network* connects end system to router
 - ❖ via base station aka "access point"
- ❑ **wireless LANs:**
 - ❖ 802.11b/g (WiFi): 11 or 54 Mbps
- ❑ **wider-area wireless access**
 - ❖ provided by telco operator
 - ❖ ~1Mbps over cellular system (EVDO, HSDPA)
 - ❖ next up (?): WiMAX (10's Mbps) over wide area




Introduction 1-24

Home networks

Typical home network components:

- ❑ DSL or cable modem
- ❑ router/firewall/NAT
- ❑ Ethernet
- ❑ wireless access point



Introduction 1-25

Physical Media

- ❑ **Bit**: propagates between transmitter/rcvr pairs
- ❑ **physical link**: what lies between transmitter & receiver
- ❑ **guided media**:
 - ❖ signals propagate in solid media: copper, fiber, coax
- ❑ **unguided media**:
 - ❖ signals propagate freely, e.g., radio

Twisted Pair (TP)

- ❑ two insulated copper wires
 - ❖ Category 3: traditional phone wires, 10 Mbps Ethernet
 - ❖ Category 5: 100Mbps Ethernet



Introduction 1-26

Physical Media: coax, fiber

Coaxial cable:

- ❑ two concentric copper conductors
- ❑ bidirectional
- ❑ baseband:
 - ❖ single channel on cable
 - ❖ legacy Ethernet
- ❑ broadband:
 - ❖ multiple channels on cable
 - ❖ HFC



Fiber optic cable:

- ❑ glass fiber carrying light pulses, each pulse a bit
- ❑ high-speed operation:
 - ❖ high-speed point-to-point transmission (e.g., 10's-100's Gps)
- ❑ low error rate: repeaters spaced far apart ; immune to electromagnetic noise



Introduction 1-27

Physical media: radio

- ❑ signal carried in electromagnetic spectrum
- ❑ no physical "wire"
- ❑ bidirectional
- ❑ propagation environment effects:
 - ❖ reflection
 - ❖ obstruction by objects
 - ❖ interference

Radio link types:

- ❑ **terrestrial microwave**
 - ❖ e.g. up to 45 Mbps channels
- ❑ **LAN** (e.g., Wifi)
 - ❖ 11Mbps, 54 Mbps
- ❑ **wide-area** (e.g., cellular)
 - ❖ 3G cellular: ~ 1 Mbps
- ❑ **satellite**
 - ❖ Kbps to 45Mbps channel (or multiple smaller channels)
 - ❖ 270 msec end-end delay
 - ❖ geosynchronous versus low altitude


Introduction 1-28

Chapter 1: roadmap

- 1.1 What *is* the Internet?
- 1.2 Network edge
 - end systems, access networks, links
- 1.3 Network core
 - circuit switching, packet switching, network structure
- 1.4 Delay, loss and throughput in packet-switched networks
- 1.5 Protocol layers, service models

The Network Core


- mesh of interconnected routers
- *the fundamental question*: how is data transferred through net?
 - ❖ circuit switching: dedicated circuit per call: telephone net
 - ❖ packet-switching: data sent thru net in discrete "chunks"



Network Core: Circuit Switching

End-end resources reserved for "call"

- link bandwidth, switch capacity
- dedicated resources: no sharing
- circuit-like (guaranteed) performance
- call setup required




Network Core: Circuit Switching

- network resources (e.g., bandwidth) divided into "pieces"
- pieces allocated to calls
- resource piece *idle* if not used by owning call (*no sharing*)

- dividing link bandwidth into "pieces"
 - ❖ frequency division
 - ❖ time division

Circuit Switching: FDM and TDM



Introduction 1-33

Numerical example

- How long does it take to send a file of 640,000 bits from host A to host B over a circuit-switched network?
 - ❖ All links are 1.536 Mbps
 - ❖ Each link uses TDM with 24 slots/sec
 - ❖ 500 msec to establish end-to-end circuit

Let's work it out!

Introduction 1-34

Network Core: Packet Switching

each end-end data stream divided into *packets*

- user A, B packets *share* network resources
- each packet uses full link bandwidth
- resources used *as needed*

resource contention:


- aggregate resource demand can exceed amount available
- congestion: packets queue, wait for link use
- store and forward: packets move one hop at a time
 - ❖ Node receives complete packet before forwarding

Bandwidth division into "pieces"
 Dedicated allocation
 Resource reservation



Introduction 1-35


Packet Switching: Statistical Multiplexing



Sequence of A & B packets does not have fixed pattern, bandwidth shared on demand → **statistical multiplexing**.
 TDM: each host gets same slot in revolving TDM frame.

Introduction 1-36

Packet-switching: store-and-forward




- takes L/R seconds to transmit (push out) packet of L bits on to link at R bps
 - *store and forward*: entire packet must arrive at router before it can be transmitted on next link
 - delay = $3L/R$ (assuming zero propagation delay)
- Example:**
- $L = 7.5$ Mbits
 - $R = 1.5$ Mbps
 - transmission delay = 15 sec
- } more on delay shortly ...

Packet switching versus circuit switching

Packet switching allows more users to use network!

- 1 Mb/s link
- each user:
 - ❖ 100 kb/s when "active"
 - ❖ active 10% of time
- *circuit-switching*:
 - ❖ 10 users
- *packet switching*:
 - ❖ with 35 users, probability > 10 active at same time is less than .0004



Q: how did we get value 0.0004?

Packet switching versus circuit switching


Is packet switching a "slam dunk winner?"

- great for bursty data
 - ❖ resource sharing
 - ❖ simpler, no call setup
- *excessive congestion*: packet delay and loss
 - ❖ protocols needed for reliable data transfer, congestion control
- Q: *How to provide circuit-like behavior?*
 - ❖ bandwidth guarantees needed for audio/video apps
 - ❖ still an unsolved problem (chapter 7)


Q: human analogies of reserved resources (circuit switching) versus on-demand allocation (packet-switching)?

Internet structure: network of networks

- roughly hierarchical
- *at center*: "tier-1" ISPs (e.g., Verizon, Sprint, AT&T, Cable and Wireless), national/international coverage
 - ❖ treat each other as equals




Tier-1 ISP: e.g., Sprint




Internet structure: network of networks

- "Tier-2" ISPs: smaller (often regional) ISPs
 - ❖ Connect to one or more tier-1 ISPs, possibly other tier-2 ISPs




Internet structure: network of networks

- "Tier-3" ISPs and local ISPs
 - ❖ last hop ("access") network (closest to end systems)



Internet structure: network of networks

- a packet passes through many networks!




Chapter 1: roadmap

- 1.1 What *is* the Internet?
- 1.2 Network edge
 - end systems, access networks, links
- 1.3 Network core
 - circuit switching, packet switching, network structure
- 1.4 Delay, loss and throughput in packet-switched networks
- 1.5 Protocol layers, service models


How do loss and delay occur?

- packets *queue* in router buffers
- packet arrival rate to link exceeds output link capacity
- packets queue, wait for turn



Four sources of packet delay


- 1. nodal processing:
 - ❖ check bit errors
 - ❖ determine output link
- 2. queueing
 - ❖ time waiting at output link for transmission
 - ❖ depends on congestion level of router




Delay in packet-switched networks

- 3. Transmission delay:
 - R = link bandwidth (bps)
 - L = packet length (bits)
 - time to send bits into link = L/R
- 4. Propagation delay:
 - d = length of physical link
 - s = propagation speed in medium ($\sim 2 \times 10^8$ m/sec)
 - propagation delay = d/s

Note: s and R are very different quantities!




Caravan analogy



- cars "propagate" at 100 km/hr
- toll booth takes 12 sec to service car (transmission time)
- car~bit; caravan ~ packet
- Q: How long until caravan is lined up before 2nd toll booth?
- Time to "push" entire caravan through toll booth onto highway = $12 \times 10 = 120$ sec
- Time for last car to propagate from 1st to 2nd toll booth: $100\text{km}/(100\text{km/hr}) = 1$ hr
- A: 62 minutes

Caravan analogy (more)



- Cars now "propagate" at 1000 km/hr
- Toll booth now takes 1 min to service a car
- Q: Will cars arrive to 2nd booth before all cars serviced at 1st booth?
- Yes! After 7 min, 1st car at 2nd booth and 3 cars still at 1st booth.
- 1st bit of packet can arrive at 2nd router before packet is fully transmitted at 1st router!
 - ❖ See Ethernet applet at AWL Web site

Nodal delay


$$d_{\text{nodal}} = d_{\text{proc}} + d_{\text{queue}} + d_{\text{trans}} + d_{\text{prop}}$$

- d_{proc} = processing delay
 - ❖ typically a few microseconds or less
- d_{queue} = queuing delay
 - ❖ depends on congestion
- d_{trans} = transmission delay
 - ❖ = L/R , significant for low-speed links
- d_{prop} = propagation delay
 - ❖ a few microseconds to hundreds of msecs

Queueing delay (revisited)

- R =link bandwidth (bps)
- L =packet length (bits)
- a =average packet arrival rate


traffic intensity = La/R



- $La/R \sim 0$: average queueing delay small
- $La/R \rightarrow 1$: delays become large
- $La/R > 1$: more "work" arriving than can be serviced, average delay infinite!

"Real" Internet delays and routes

- What do "real" Internet delay & loss look like?
- **Traceroute program:** provides delay measurement from source to router along end-end Internet path towards destination. For all i :
 - ❖ sends three packets that will reach router i on path towards destination
 - ❖ router i will return packets to sender
 - ❖ sender times interval between transmission and reply.



Introduction 1-53

"Real" Internet delays and routes

traceroute: gaia.cs.umass.edu to www.eurecom.fr

Three delay measurements from gaia.cs.umass.edu to cs-gw.cs.umass.edu

1	cs-gw (128.119.240.254)	1 ms	1 ms	2 ms
2	border1-rt-ia5-1-0.gw.umass.edu (128.119.3.145)	1 ms	1 ms	2 ms
3	cht-vbns.gw.umass.edu (128.119.3.130)	6 ms	5 ms	5 ms
4	jn1-at1-0-0-19.wor.vbns.net (204.147.132.129)	16 ms	11 ms	13 ms
5	jn1-so7-0-0-0.wae.vbns.net (204.147.136.136)	21 ms	18 ms	18 ms
6	abilene-vbns.abilene.ucaid.edu (198.32.11.9)	22 ms	18 ms	22 ms
7	nycm-wash.abilene.ucaid.edu (198.32.8.46)	22 ms	22 ms	22 ms
8	62.40.103.253 (62.40.103.253)	104 ms	109 ms	106 ms
9	de2-1.de1.de.geant.net (62.40.96.129)	109 ms	102 ms	104 ms
10	de.fr1.fr.geant.net (62.40.96.50)	113 ms	121 ms	114 ms
11	renater-gw.fr1.fr.geant.net (62.40.103.54)	112 ms	114 ms	112 ms
12	nio-n2.cssi.renater.fr (193.51.206.13)	111 ms	114 ms	116 ms
13	nice.cssi.renater.fr (195.220.98.102)	123 ms	125 ms	124 ms
14	r3t2-nice.cssi.renater.fr (195.220.98.110)	126 ms	126 ms	124 ms
15	eurecom-valbonne.r3t2.ft.net (193.48.50.54)	135 ms	128 ms	133 ms
16	194.214.211.25 (194.214.211.25)	126 ms	128 ms	126 ms
17	***			
18	***			
19	fantasia.eurecom.fr (193.55.113.142)	132 ms	128 ms	136 ms


trans-oceanic link

* means no response (probe lost, router not replying)

Introduction 1-54

Packet loss


- queue (aka buffer) preceding link in buffer has finite capacity
- packet arriving to full queue dropped (aka lost)
- lost packet may be retransmitted by previous node, by source end system, or not at all



Introduction 1-55

Throughput


- **throughput:** rate (bits/time unit) at which bits transferred between sender/receiver
 - ❖ **instantaneous:** rate at given point in time
 - ❖ **average:** rate over long(er) period of time




Introduction 1-56

Throughput (more)

- $R_s < R_c$ What is average end-end throughput?



- $R_s > R_c$ What is average end-end throughput?




bottleneck link

link on end-end path that constrains end-end throughput

Throughput: Internet scenario

- per-connection end-end throughput: $\min(R_c, R_s, R/10)$
- in practice: R_c or R_s is often bottleneck



10 connections (fairly) share backbone bottleneck link R bits/sec

Chapter 1: roadmap

- 1.1 What *is* the Internet?
- 1.2 Network edge
 - end systems, access networks, links
- 1.3 Network core
 - circuit switching, packet switching, network structure
- 1.4 Delay, loss and throughput in packet-switched networks
- 1.5 Protocol layers, service models

Protocol "Layers"

Networks are complex!


- many "pieces":
 - ❖ hosts
 - ❖ routers
 - ❖ links of various media
 - ❖ applications
 - ❖ protocols
 - ❖ hardware, software

Question:

Is there any hope of *organizing* structure of network?


Or at least our discussion of networks?

Organization of air travel



- a series of steps

Layering of airline functionality



Layers: each layer implements a service

- ❖ via its own internal-layer actions
- ❖ relying on services provided by layer below


Why layering?

Dealing with complex systems:

- explicit structure allows identification, relationship of complex system's pieces
 - ❖ layered **reference model** for discussion
- modularization eases maintenance, updating of system
 - ❖ change of implementation of layer's service transparent to rest of system
 - ❖ e.g., change in gate procedure doesn't affect rest of system
- layering considered harmful?


Internet protocol stack

- **application:** supporting network applications
 - ❖ FTP, SMTP, HTTP
- **transport:** process-process data transfer
 - ❖ TCP, UDP
- **network:** routing of datagrams from source to destination
 - ❖ IP, routing protocols
- **link:** data transfer between neighboring network elements
 - ❖ PPP, Ethernet
- **physical:** bits "on the wire"




ISO/OSI reference model

- **presentation:** allow applications to interpret meaning of data, e.g., encryption, compression, machine-specific conventions
- **session:** synchronization, checkpointing, recovery of data exchange
- Internet stack "missing" these layers!
 - ❖ these services, *if needed*, must be implemented in application
 - ❖ needed?



Encapsulation



Introduction: Summary

Covered a "ton" of material!

- Internet overview
- what's a protocol?
- network edge, core, access network
 - ❖ packet-switching versus circuit-switching
 - ❖ Internet structure
- performance: loss, delay, throughput
- layering, service models
- security
- history

You now have:

- context, overview, "feel" of networking
- more depth, detail to follow!